

Cables

Category 6A Cable 4 Pair


Description

- Capable of handling full broadband and baseband
- High flame retardant grade to minimize the risk of fire propagation
- Comply with ANSI/TIA - 568 - C.2 standard
- Horizontal Distribution & Backbone Cabling
- 10/100/1000/10G BASE-T (IEEE 802.3)
- POE ++ (IEEE 802.3 bt draft. Type 3(60W) or Type 4(100W))

Features



Category 6A U/UTP Cable 4Pair Inner Jacket Spacer

- Inner Jacket Spacer Sheath
- Cable Out Diameter : 8.4mm
- UL Listed & ETL Verified
- 23AWG Solid Copper





Category 6A U/UTP Cable 4Pair Segmented Tape Type

- LS Unique Segmented Tape Type
- Cable Out Diameter : 6.8mm
- UL Listed & ETL Verified
- 23AWG Solid Copper




Category 6A U/UTP Slim Cable 4Pair Segmented Tape Type

- LS Unique Segmented Tape Type
- Cable Out Diameter : 5.8mm
- 70m Category 6A Channel Support
- 26AWG Solid Copper




Category 6A F/UTP Cable 4Pair Shielded

- Aluminum Foiled Shield
- Cable Out Diameter : 7.2mm
- UL Listed
- 23AWG Solid Copper



Category 6A U/FTP Cable 4Pair PiMF Shielded

- PiMF (pair in metal foil)
- Cable Out Diameter : 7.2mm
- Electrical Performance IEC 61156-5
- 23AWG Solid Copper



*PiMF : Pair In Metal Foil

Part Numbers

Description		Flame Retardant Grade				
		CMX	CM	CMR	CMP	LSZH
Category 6A U/UTP Cable 4 Pair	Original : 8.4mm	UTP-A-C6G-E1VI-X 0.5X004P/xx	UTP-A-C6G-E1VI-M 0.5X004P/xx	UTP-A-C6G-E1VI-R 0.5X004P/xx	UTP-A-C6G-F1VI-P 0.5X004P/xx	UTP-A-C6G-E1ZI-X 0.5X004P/xx
	Next G : 6.8mm	UTP-A-C6G-E1VF-X 0.5X004P/xx	UTP-A-C6G-E1VF-M 0.5X004P/xx	UTP-A-C6G-E1VF-R 0.5X004P/xx	-	UTP-A-C6G-E1ZF-X 0.5X004P/xx
	USS: 5.8mm	UTP-A-C6G-E1VL-X 26AWGx004P/xx	UTP-A-C6G-E1VL-M 26AWGx004P/xx	UTP-A-C6G-E1VL-R 26AWGx004P/xx	-	UTP-A-C6G-E1ZL-X 26AWGx004P/xx
Category 6A U/FTP Cable 4 Pair		USP-A-C6G-E1VN-X 0.5X004P/xx	USP-A-C6G-E1VN-M 0.5X004P/xx	USP-A-C6G-E1VN-R 0.5X004P/xx	-	USP-A-C6G-E1ZN-X 0.5X004P/xx
Category 6A F/UTP Cable 4 Pair		FTP-A-C6G-E1VN-X 0.5X004P/xx	FTP-A-C6G-E1VN-M 0.5X004P/xx	FTP-A-C6G-E1VN-R 0.5X004P/xx	-	FTP-A-C6G-E1ZN-X 0.5X004P/xx

xx denotes color: WH=White, BL=Blue, GY=Gray, VI=Violet, OR=Orange, RD=Red, GN=Green, YL=Yellow, BK=Black